

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

BSM-0110 Product Size: NPS 18 STD Production Date: 2011 Nov 22

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Heat Number:

Product Standards: ASTM/ASME A/SA106-2010 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 18 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0110 (PIPE # LENGTH MASS) NDE 1030PSI NACE MR0175 2011/11 MADE IN CANADA.

| BSM-0110 | Heat | | |
|-------------|-------------|-----------|----------------|
| Heat | Test Type | | |
| 18 | NPS | | P |
| STD | SCH | | Product Detail |
| Ц | Pieces | | S |
| DRL | Length | | |
| 2788 LB | Mass | | |
| 5 | μR/hr | Geiger | |
| <20 | Gauss | Res.Mag. | |
| Pass | Insp. | Visual | |
| Pass | OD | | Non-E |
| Pass | WT | TU | Destructive 1 |
| 1 | ASTM E213 | TU | esting |
| Pass | ASTM E309 | ET | |
| Pass | 1030 psi/5s | HydroTest | |
| 37.5° Bevel | Condition | End | |

| BSM-0110 | Heat | | |
|------------------------|---------------------------|---|------------|
| Heat | Test Type | | |
| Refining; Vacuum Degas | Blast Furnace; EAF; Ladle | Steelmaking Method | |
| 0.20 | С | | |
| 0.87 | Mn | | |
| 0.015 | P | | |
| 0.015 0.010 | S | | Chemical A |
| 0.21 | Si | | Analysis |
| 0.03 | Cr | | (wt%) |
| 0.11 | Cu | | |
| 0.01 | Mo | | |
| 0.04 | Ni | | |
| 0.002 | ٧ | 500000000000000000000000000000000000000 | |
| 0.001 | Ti | | |
| 0.001 | Nb | | |
| 0.0001 | В | | |
| 0.36 | (IIW) | CE | |
| 0.37 | (CSA) | Œ | |

| | | | | Mechan | Mechanical Properties | | | | | |
|----------|-----------|--------------------|----------|-----------------|-----------------------|---------------|---------------|--------------|------------|----------------|
| | | | Hardness | | Tension Test | Yield (Rt0.5) | Yield (Rp0.2) | Tensile (Rm) | 1/4 | Elongation (A) |
| Heat | Test Type | Microstructure | HRBW | Flattening Test | 50mm GL; 38mm x WT | psi | psi | psi | (Rt0.5/Rm) | % |
| BSM-0110 | Heat | Ferrite & Pearlite | 79 | Pass | Transverse | 46,700 | 46,700 | 74,500 | 0.63 | 36 |
| | | | | | Longitudinal | 49,400 | 49,700 | 75,500 | 0.65 | 41 |

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2010, A/SA53-2010 and the purchase order requirements, and that the 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product. This product has no mercury contamination

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

2011 Dac 13