

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Mill Test Certificate

Product Heat Number: BSM-0116 Product Size: NPS 18 STD Production Date: 2011 Nov 24

Production Method: Hot Expansion Product Heat Treatment: As-rolled

Product:

Seamless Carbon Steel Pipe

Product Standards: ASTM/ASME A/SA106-2010 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 18 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0116 (PIPE # LENGTH MASS) NDE 1030PSI NACE MR0175 2011/11 MADE IN CANADA.

| _ | _ | | |
|-------------|------------------------|-----------|---------------|
| BSM-0116 | Heat | | |
| Heat | Test Type | | |
| 18 | NPS | | P |
| STD | SCH | | Product Detai |
| ω | Pieces | | ils |
| DRL | Length | | |
| 8450 LB | Mass | | |
| <5 | μR/hr | Geiger | |
| <20 | Gauss | Res.Mag. | |
| Pass | Insp. | Visual | |
| Pass | OD | | Non-D |
| Pass | TW | TU | Destructive T |
| - | ASTM E213 A | TU | esting |
| Pass | | ET | |
| Pass | STM E309 1030 psi/5s (| HydroTest | |
| 37.5° Bevel | /5s Condition | End | |

| | 1 | _ | Т |
|------------------------|---------------------------|--------------------|---------------------|
| BSM-0116 | | | |
| Heat | Test Type | | |
| Refining; Vacuum Degas | Blast Furnace; EAF; Ladle | Steelmaking Method | |
| 0.21 | 0 | | |
| 0.88 | Mn | | |
| 0.012 | P | | |
| 0.010 | S | | Chemica |
| 0.21 | Si | | ical Analysis (wt%) |
| 0.03 | C, | | (wt%) |
| 0.10 | Cn | | |
| 0.01 | Mo | | |
| 0.03 | Z. | | |
| 0.003 | < | | |
| 0.001 | П | | |
| 0.001 | Nb | | |
| 0.0001 | В | | |
| 0.37 | (IIW) | Œ | |
| 0.38 | (CSA) | CE | |

| | BSM- | H6 | | |
|--------------|--------------------|------------------------------------|----------------|--|
| | BSM-0116 Heat | Heat | | |
| | Heat | Test Type | | |
| | Ferrite & Pearlite | Microstructure | | The state of the s |
| | 80 | HRBW | Hardness | |
| | Pass | Flattening Test | 8 | Mechan |
| Longitudinal | Transverse | Flattening Test 50mm GL; 38mm x WT | Tension Test | Mechanical Properties |
| 49,000 | 50,500 | psi | Yield (Rt0.5) | |
| 49,500 | 50,500 | psi | Yield (Rp0.2) | |
| 76,500 | 78,000 | psi | Tensile (Rm) | |
| 0.64 | 0.65 | (Rt0.5/Rm) | Υ/Τ | |
| 38 | 39 | % | Elongation (A) | |

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2010, A/SA53-2010 and the purchase order requirements, and that the results meet the corresponding requirements. We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product. This product has no mercury contamination.

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.

ZOILDec 2