

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0118

Product Size:

Mill Test Certificate

NPS 18 STD

Production Date: 2011 Nov 28

Production Method: **Hot Expansion**

Product Heat Treatment: As-rolled

Product Standards: ASTM/ASME A/SA106-2010 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 18 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0118 (PIPE # LENGTH MASS) NDE 1030PSI NACE MR0175 2011/11 MADE IN CANADA.

Product Details Non-Destructive Testing HydroTest End HydroTest End HydroTest End HydroTest End Heat Test Type NPS SCH Pieces Length Mass μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s Condition Condition
Product Details Non-Destructive Testing
Product Details Non-Destructive Testing
S Non-Destructive Testing Fieces Length Mass μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s 7 DRL 19,687 LB <5 <20 Pass Pass Pass Pass Pass
S Non-Destructive Testing Fieces Length Mass μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s 7 DRL 19,687 LB <5 <20 Pass Pass Pass Pass Pass
Non-Destructive Testing Geiger Res.Mag. Visual UT UT ET HydroTest Nass μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s 19,687 LB <5 <20 Pass Pass Pass Pass Pass
Non-Destructive Testing Geiger Res.Mag. Visual UT UT ET HydroTest μR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s LB <5
Res.Mag. Visual Gauss Insp. OD Pass Pass Pass Pass Pass Pass Pass P
Visual UT UT ET HydroTest Insp. OD WT ASTM E213 ASTM E309 1030 psi/5s Pass Pass Pass Pass Pass
Non-Destructive Testing UT UT ET HydroTest OD WT ASTM E213 ASTM E309 1030 psi/5s Pass Pass Pass Pass Pass Pass
Dn-Destructive Testing UT UT UT ET HydroTest WT ASTM E213 ASTM E309 1030 psi/5s Pass Pass Pass Pass
ructive Testing UT UT UT ET HydroTest WT ASTM E213 ASTM E309 1030 psi/5s Pass Pass Pass Pass
JT ET HydroTest 1E213 ASTM E309 1030 psi/5s Pass Pass
HydroTest 309 1030 psi/5s Pass
roTest) psi/5s ass
End Condition 37.5° Bevel

	_	_	_	_
	BSM-0118	Heat		
	Heat	Test Type		
	Refining; Vacuum Degas	Blast Furnace; EAF; Ladle	Steelmaking Method	
	0.22	C		
	0.88	Mn		
	0.012	ъ		
	0.008	S		Chemical
	0.21	Si		ical Analysis (wt%)
	0.03	ڻ د		(wt%)
	0.10	Cn		
	0.01	Mo		
	0.03	<u>Z</u> ,		
	0.003	٧		
	0.001	Ti		
	0.001	Nb		
	0.0001	В		
	0.38	(IIW)	Œ	
22410000	0.39	(CSA)	Œ	

		Т		Τ-
	BSM-0118	Heat		
	Heat	Test Type		
	Ferrite & Pearlite	Microstructure		
	78	HRBW	Hardness	
	Pass	Flattening Test		Mechan
Longitudinal	Transverse	Flattening Test 50mm GL; 38mm x WT	Tension Test	Mechanical Properties
47,700	48,000	psi	Yield (Rt0.5)	
48,600	48,000	psi	Yield (Rp0.2)	
74,500	76,500	psi	Tensile (Rm)	
0.64	0.63	(Rt0.5/Rm)	1/4	
42	42	%	Elongation (A)	

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2010, A/SA53-2010 and the purchase order requirements, and that the results meet the corresponding requirements. We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product. This product has no mercury contamination

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

2011 Dec

Manager of Quality and R&D