

## Mill Test Certificate

**Bri-Steel Manufacturing Inc.** 

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0150

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Size:

NPS 30 STD

Production Date: 2011 Dec 15

Product Standards: ASTM/ASME A/SA106-2010 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 30 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0150 (PIPE # LENGTH MASS) NDE 630PSI NACE MR0175 2011/11 MADE IN CANADA.

|             | _  |  | _  |
|-------------|--|--|--|
| BSM-0150    | Heat   |  |  |
| Heat        | Test Type  |  |  |
| 30          | NPS  |  | P  |
| STD         | SCH  |  | Product Detail   |
| 00          | Pieces   |  | ils  |
| DRL         | Length   |  |  |
| 118.6       | lb/ft  | Mass   |  |
| \$          | μR/hr  | Geiger   |  |
| <20         | Gauss  | Res.Mag.   |  |
| Pass        | Insp.  | Visual   |  |
| Pass        | OD   |  | Non-D  |
| Pass        | ΨT   | TU   | Destructive Testin   |
| 1           | ASTM E213  | TU   | esting   |
| Pass        | ASTM E309  | ET   |  |
| Pass        | 630 psi/5s   | HydroTest  |  |
| 37.5° Bevel | Condition  | End  |  |
|             | 30 STD 8 DRL 118.6 <5 <20 Pass Pass Pass Pass Pass | Test Type NPS SCH Pieces Length lb/ft µR/hr Gauss Insp. OD WT ASTM E213 ASTM E309 630 psi/5s Heat 30 STD 8 DRL 118.6 <5 <20 Pass Pass Pass Pass Pass | Test TypeNPSSCHPiecesLengthlb/ftμR/hrGaussVisualUTUTUTHeat30STD8DRL118.6<5 |

| BSM-0150               | Heat                      |                    |                  |
|------------------------|---------------------------|--------------------|------------------|
| Heat                   | Test Type                 |                    |                  |
| Refining; Vacuum Degas | Blast Furnace; EAF; Ladle | Steelmaking Method |                  |
| 0.21                   | С                         |                    |                  |
| 0.90                   | Mn                        |                    |                  |
| 0.90 0.015             | P                         |                    |                  |
| 0.005                  | S                         |                    | Chemical,        |
| 0.24                   | Si                        |                    | l Analysis (wt%) |
| 0.04                   | Ç                         |                    | (wt%)            |
| 0.06                   | Cu                        |                    |                  |
| 0.01                   | Mo                        |                    |                  |
| 0.03                   | <u>z</u> .                |                    |                  |
| 0.005                  | <                         |                    |                  |
| 0.002                  | П                         |                    |                  |
| 0.001                  | Nb                        |                    |                  |
| 0.0001                 | В                         |                    |                  |
| 0.38                   | (IIW)                     | Œ                  |                  |
| 0.38                   | (CSA)                     | CE                 |                  |

|    |              | _                  | _                                  |                | _                     |
|----|--------------|--------------------|------------------------------------|----------------|-----------------------|
|    |              | BSM-0150           | Heat                               |                |                       |
|    |              | Heat               | Test Type                          |                |                       |
|    |              | Ferrite & Pearlite | Microstructure                     |                |                       |
|    |              | 77                 | HRBW                               | Hardness       |                       |
| 75 |              | Pass               | Flattening Test                    |                | Mechan                |
|    | Longitudinal | Transverse         | Flattening Test 50mm GL; 38mm x WT | Tension Test   | Mechanical Properties |
|    | 48,000       | 45,400             | psi                                | Yield (Rt0.5)  |                       |
|    | 47,700       | 44,000             | psi                                | Yield (Rp0.2)  |                       |
|    | 74,500       | 74,000             | psi                                | Tensile (Rm)   |                       |
|    | 0.64         | 0.61               | (Rt0.5/Rm)                         | Υ/Τ            |                       |
|    | 40           | 42                 | %                                  | Elongation (A) |                       |

Additional Details:

Inc. in accordance with ASTM/ASME A/SA106-2010, A/SA53-2010 and the purchase order requirements, and that the results meet the corresponding requirements.  $\checkmark~$  We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. ✓ This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

 $\checkmark$  No weld repairs have been performed on this product. This product has no mercury contamination

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

As per client requirements, diameter does not exceed 30.250 inches

Mill Test Certificate approved by:

2012 Febs

Manager of Quality and R&D Kenton Dechant, P.Eng.