

Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0225

Product Size:

NPS 24 STD

Production Date:

February 23, 2012

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Standards: ASTM/ASME A/SA106-2011 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 24 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0225 (PIPE # LENGTH MASS) NDE 740PSI NACE MR0175 2012/02 MADE IN CANADA.

| | <u></u> | , | | | | | Г |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|--------|------------|-------|-----------|---|----------------|
| | BSM-0225 | 2000 | неат | | | | |
| | Heat | | lest Type | There | | | |
| | 24 | | NPS | | | | P |
| | STD | | SCH | 0 | | | Product Detail |
| | 1- | | Pieces | ! | | | ils |
| | DRL | | Length | | | | |
| | 94.62 | | lb/ft | | Mass | | |
| Control of the Contro | \$ | | LR/hr | | Geiger |) | |
| | <20 | | Gauss | 36 | Res.Mag. | | |
| | Pass | | insp. | | Visual | | |
| | Pass | | 8 | | | | Non-I |
| | Pass | | _ ≼ | | T | | Destructive ' |
| | 1 | | ASTM E213 | | TU | | Testing |
| | Pass | | ASTM F309 | | E | | |
| | Pass | | 740 nsi/5s | | HydroTest | | |
| | 37.5° Bevel | COLLOS | Condition | | End | | |

| משלט-טבעבט | DCV VODE | неат | | | | |
|-------------------------|----------|---------------------------|--------|--------------------|---|----------|
| Liegi | L 02+ | lest Type | 1 | | | |
| nellillig, vacuum Degas | - | Blast Furnace; EAF; Ladle | , , | Steelmaking Method | | |
| 17.0 | 2 | 0 | | | | |
| 0.88 | 3 | S | | | | |
| 0.014 | 2 | Р | 2000 | | | |
| 0.004 | 2 | S | | | | Chemical |
| 0.26 | | <u>s</u> | 900000 | | 1 | Analysis |
| 0.05 | | J. | 585 | | 1 | (wt%) |
| 0.12 | | 5 | | | | |
| 0.04 | | ≤ o | | | | |
| 0.04 | | Z | | | | |
| 0.003 | | < | | | | |
| 0.001 | | _! | | | | |
| 0.002 | | Z S | | | | |
| 0.0001 | [| D | | | | |
| 0.39 | | | - | ÇF | | |
| 0.39 | 100,1 | (050) | () | ÇF | | |

| CZZN-IAICO | 2000 | Heat | | |
|-------------------|------|--------------------|----------------|-----------------------|
| неас | | lest lype | 1 | |
| remite & Pearlite | | Microstructure | | |
| 81 | | HRBW | Hardness | |
| Pass | | Flattening Test | | Mechan |
| Transverse | | 50mm GL; 38mm x WT | Tension Test | Mechanical Properties |
| 42,700 | | psi. | Yield (Rt0.5) | |
| 42,700 | | DSi. | Yield (Rp0.2) | |
| 76,000 | Par. | DSi. | Tensile (Rm) | |
| 0.56 | 1 | (Rt0.5/Rm) | 1/4 | |
| 46 | ,,, | % | Elongation (A) | |

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2010 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1 This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product. This product has no mercury contamination

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

2012 Mar 7

Manager of Quality and R&D