

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number: BSM-0242

Product Size:

NPS 24 STD

Production Date:

March 1, 2012

Production Method: Hot Expansion

Product Standards:

Product Heat Treatment: As-rolled

ASTM/ASME A/SA106-2011 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

Product Markings: .BRI-STEEL MFG NPS 24 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0242 (PIPE # LENGTH MASS) NDE 740PSI NACE MR0175 2012/03 MADE IN CANADA.

|        | _           | Т          |           | т-             |
|--------|-------------|------------|-----------|----------------|
|        | BSM-0242    | Heat       |           |                |
|        | Heat        | Test Type  |           |                |
|        | 24          | NPS        |           | P              |
|        | STD         | SCH        |           | Product Detail |
|        | 4           | Pieces     |           | ils            |
|        | DRL         | Length     |           |                |
| 5080   | 94.62       | lb/ft      | Mass      |                |
|        | <b>\$</b> 5 | μR/hr      | Geiger    |                |
| 000000 | <20         | Gauss      | Res.Mag.  |                |
|        | Pass        | insp.      | Visual    |                |
|        | Pass        | OD         |           | Non-I          |
|        | Pass        | WT         | TU        | Destructive 1  |
|        |             | ASTM E213  | TU        | esting         |
|        | Pass        | ASTM E309  | ET        |                |
|        | Pass        | 740 psi/5s | HydroTest |                |
|        | 37.5° Bevel | Condition  | End       |                |

|       | BSIVI-0242   Heat   Refining; Vacuum Degas |        | lest Type    | Test Type    | Test Type  | Test Type |
|-------|--------------------------------------------|--------|--------------|--------------|------------|-----------|
|       | 0.21                                       |        | С            | C            | 0          | С         |
| r     | 0.89 0.03                                  |        | Mn           | Mn P         | Mn         | Mn P      |
| 0.000 | 0.012   0.009                              |        | S            | S            | S          | S         |
| r     | 0.25                                       |        | Si           | Si           | Si         | Si        |
| r     | 0.03                                       |        | <del>ر</del> | <del>ر</del> | ç          | ς,        |
|       | 0.12                                       |        | <u>ნ</u>     | <u>ნ</u>     | C          | 5         |
|       | 0.02                                       |        | 200          | S<br>o       | <u>S</u>   | <u>S</u>  |
|       | 0.04                                       |        | <u>z</u>     | <u>Z</u> .   | <u>Z</u> . | <u>z</u>  |
| 1     | 0.004                                      | ٧      | <            | <            | <          | <         |
|       | 0.001                                      | =      | _!           | 4            | <u>:</u> ! | :         |
|       | 0.002                                      | ī      | 25           | <u> </u>     | <u></u>    | <u> </u>  |
|       | 0.0001                                     | 0      | 0            | 0            | 0          | •         |
| 0,00  | 0.38                                       | (1100) | (111/1)      | (111)        | CE         | CE        |
| 0.00  | 0 39                                       |        | 1000         | ()           | (E)        | (SC)      |

|              | BSM-0242 Heat      | Heat                               |                |                       |
|--------------|--------------------|------------------------------------|----------------|-----------------------|
|              | Heat               | Test Type                          |                |                       |
|              | Ferrite & Pearlite | Microstructure                     |                |                       |
|              | 77                 | HRBW                               | Hardness       |                       |
|              | Pass               | Flattening Test                    |                | Mechan                |
| Longitudinal | Transverse         | Flattening Test 50mm GL; 38mm x WT | Tension Test   | Mechanical Properties |
| 47,500       | 45,200             | psi                                | Yield (Rt0.5)  |                       |
| 47,300       | 44,300             | psi                                | Yield (Rp0.2)  |                       |
| <br>73,000   | 72,500             | psi                                | Tensile (Rm)   |                       |
| 0.65         | 0.62               | (Rt0.5/Rm)                         | Υ/Τ            |                       |
| 41           | 43                 | %                                  | Elongation (A) |                       |

## Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2010 and the purchase order requirements, and that the ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Mill Test Certificate approved by:

- Service, and NACE MR0103-2010 Section 2.1. This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour
- $\prime$  No weld repairs have been performed on this product. This product has no mercury contamination

This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Manager of Quality and R&D Kenton Dechant, P.Eng.

2012Mar15