

## Mill Test Certificate

Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Fax: 001 (780) 469-6986

www.brichemsteel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-0299

Product Size: NPS 24 STD

Production Date:

April 24, 2012

Production Method: Hot Expansion

Product Heat Treatment: As-rolled

Product Standards: ASTM/ASME A/SA106-2011 Grade B/C, A/SA53-2010 Grade B Type S, NACE MR0175-2009

**Product Markings:** .BRI-STEEL MFG NPS 24 STD ASTM/ASME A/SA106 GR B/C A/SA53 GR B HEAT BSM-0299 (PIPE # LENGTH MASS) 94.621b/ft NDE 740PSI NACE MR0175 2012/04 MADE IN CANADA.

|             | Т          |           | Т              |
|-------------|------------|-----------|----------------|
| BSM-0299    | Heat       | •         |                |
| Heat        | Test Type  | ı         |                |
| 24          | NPS        |           | -              |
| STD         | SCH        |           | Product Detail |
| ω           | Pieces     |           | Ils            |
| DRL         | Length     |           |                |
| 94.62       | lb/ft      | Mass      |                |
| S           | μR/hr      | Geiger    |                |
| <20         | Gauss      | Res.Mag.  |                |
| Pass        | insp.      | Visual    |                |
| Pass        | OD         |           | Non-I          |
| Pass        | WT         | TU        | Destructive '  |
|             | ASTM E213  | UT        | Testing        |
| Pass        | ASTM E309  | ET        |                |
| Pass        | 740 psi/5s | HydroTest |                |
| 37.5° Bevel | Condition  | End       |                |
|             |            |           |                |

|        | BSM-0299               | неат                      |   |                    |                  |
|--------|------------------------|---------------------------|---|--------------------|------------------|
|        | 99                     | ľ                         |   |                    |                  |
|        | Heat                   | lest Type                 |   |                    |                  |
| 0)     | Refining: Vacuum Degas | Blast Furnace; EAF; Ladle | 1 | Steelmaking Method |                  |
| 0.50   | 0 20                   | C                         |   |                    |                  |
| 0.50   | 0 90                   | Mn                        |   |                    |                  |
| 0.010  | 0013                   | Ъ                         |   |                    |                  |
| 0.010  | 0 010                  | S                         |   |                    | Chemical An      |
| 0.2.0  | 0 25                   | Si                        |   |                    | l Analysis (wt%) |
| 0.00   | 200                    | Ç                         |   |                    | (wt%)            |
| 17.0   | 011                    | Cu                        |   |                    |                  |
| 20.0   | 000                    | No                        |   |                    |                  |
| 0.03   | 0 03                   | Z.                        |   |                    |                  |
| 0.000  | 0 000                  | <                         |   |                    |                  |
| 0.001  | 0 001                  | <u> </u>                  |   |                    |                  |
| 200.0  | 2000                   | Nb                        |   |                    |                  |
| TO00.0 | 0 0001                 | В                         |   |                    |                  |
| 0.3/   | 77                     | (E)                       | ( | CF                 |                  |
| 0.38   | 200                    | (CSA)                     | ( | 유                  |                  |

|  |              | BSM-0299 Heat      | nedi                               |                |                       |
|--|--------------|--------------------|------------------------------------|----------------|-----------------------|
|  |              | Heat               | rest Type                          | 7              |                       |
|  |              | Ferrite & Pearlite | Microstructure                     |                |                       |
|  |              | 77                 | HRBW                               | Hardness       |                       |
|  |              | Pass               | Flattening Test                    |                | Mechan                |
|  | Longitudinal | Transverse         | Flattening Test 50mm GL; 38mm x WT | Tension Test   | Mechanical Properties |
|  | 47,800       | 44,400             | psi                                | Yield (Rt0.5)  |                       |
|  | 47,700       | 42,700             | psi                                | Yield (Rp0.2)  |                       |
|  | 74,500       | 74,000             | psi                                | Tensile (Rm)   |                       |
| The second secon | 0.64         | 0.60               | (Rt0.5/Rm)                         | 1/4            |                       |
|  | 40           | 43                 | %                                  | Elongation (A) |                       |

Additional Details:

results meet the corresponding requirements. Inc. in accordance with ASTM/ASME A/SA106-2011, A/SA53-2010 and the purchase order requirements, and that the We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing

Service, and NACE MR0103-2010 Section 2.1. This pipe product meet the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour

No weld repairs have been performed on this product. This product has no mercury contamination This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Manager of Quality and R&D Kenton Dechant, P.Eng.