

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc. Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.brichemsteel.com

Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1663 Product Size: 16XS

Production Date:

Feb 25, 2014

Production Method: Hot Expansion

Product Standards:

Product Heat Treatment: As-rolled

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Certificate No.: MTR- 000907

**Product Markings** 

| STEEL | CAPI & L/C No. > API SPEC 5L NPS 16 XS 0.500 INCHWT GR B/X42 PSL1 SMLS 2014/02 NDE 2240PSI MEAT BSM-1663 (PIPE # LENGTH MASS) 82.77lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1663		Heat	
Heat		Test Type	
NPS 16 XS 0.500in. WT		Product Size	Product: Details
5		Pieces	
DRL		Length	
82.77	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	Z
ı	TW	디	on-Destruc
Pass	ASTM E213	TU	Non-Destructive Testing
Pass	ASTM	티	
Pass	2240PSI/ 5 s	HydroTest	
32.5° Bevel	Condition	End	

		BSM-1663	Heat			BSM-1663		וופמנ								
Blast Furnace; EAF; Ladle Refining; Vacuum Degas; Fully Killed		Stee		Heat		iest Type										
		Steelmaking Method			NPS 16 XS 0.500in. WT		Product Size									
	Product 0.22	Heat	Test Type	Chemical A	Chemical A	Chemical A	Chemical Analysis (wt%)				VT					
	0.22	0.23	C													5
	0.86	0.87	Mn						DRL		Length					
	0.018 0.003	0.011 0.004 0.24	P						82.77	lb/ft	IVIASS					
	0.003	0.004	S					hemical A	hemical A		<b>&lt;</b> 5	μR/hr	Geiger			
	0.25		Si	nalysis (		^										
	0.07	0.07	Cr	wt%)	wt%)		<10	Gauss	Kes. Mag.							
	0.07	0.06	Си			Pass	Insp.	Visual								
	0.02	0.02	Mo			Pass		0								
	0.05	0.05	N:			ı	TW	_								
	0.002		<			Pa	ASTM									
	0.001		Ti			Pass	ASTM E213 ASTM									
	0.001		Nb			Pass		ī								
	0.002 0.001 0.001 0.0002 0.39	0.0004	В			Pass	2240 PSI/	Hydrolest								
	0.39	_	CE(IIW)								5 <sub>s</sub> (	est				
	0.39	ı	CE(IIW) CE(CSA)			32.5° Bevel	5 <sub>S</sub> Condition	End								
					S 0	_		_								

<u></u>	Т		_
BSM-1663		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
76 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
44,500	psi	Yield (Rt0.5)	
73,000	psi	Tensile (Rm)	
0.61	(Rt0.5/Rm)	1/4	
45	%	Elongation (A)	

BSM-1663			
1663		Heat	
1	Standard	Test	
4	Sample Details	Impact Test	
ď		Temp	
-	J		
1	J	Impact	
1	١	Energy	
	AVG		
	%		
,	%	% Shear	
t	%	ear	
 1	AVG		
т	mm		
ı	mm	Lateral Ex	
l	mm	Expansion	
ı	AVG		

## Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 51-45th Ed., ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Kenton Dechant, P.Eng.

2014/Naw 3

Manager of Quality and R&D