

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Fax: 001 (780) 469-6986 Tel: 001 (780) 469-6603

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-1698 Product Size: 20STD

Production Date:

Mar 12, 2014

Production Method: **Hot Expansion**

Product Standards:

Product Heat Treatment: As-rolled

Certificate No.: MTR- 000953

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A/SA106-2013 Grade B/C NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings

| STEEL | <API & L/C No. > API SPEC 5L NPS 20 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2014/03 NDE 1420PSI MASSI PARTIES HEAT BSM-1698 (PIPE # LENGTH MASS) 78.6lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA

BSM-1698		Heat	
Heat		Test Type	
NPS 20 STD 0.375in. WT		Product Size	Product: Details
12		Pieces	
DRL		Length	
78.6	lb/ft	Mass	
%	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	No
Pass	WT	TU	on-Destruct
Pass	ASTM E213 ASTM	TU	Non-Destructive Testing
Pass		ET	
Pass	1420 PSI/ 5 s Condition	HydroTest	
32.5° Bevel	Condition	End	

	BSN		
		Heat	
cesas; raily zailed	Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method	
Product	Heat	Test Type	
0.21	0.18	С	
0.90	0.86	Mn	
0.021	0.019	Р	9
0.010	0.007	S	Chemical
0.26	0.24	Si	Chemical Analysis (wt%,
0.06	0.05	Cr	wt%)
0.01	0.01	Си	
0.01		Мо	
0.04	0.04	Ni	
0.003		٧	
0.002		Ti	
0.001		dN	
0.0004		В	
0.38	1	CE(IIW)	
0.38	ete:	CE(CSA)	
	Product 0.21 0.90 0.021 0.010 0.26 0.06 0.01 0.01 0.04 0.003 0.002 0.001 0.0004 0.38	Heat 0.18 0.86 0.019 0.007 0.24 0.05 0.01 0.04 0.04 0.00 0.001 0.003 0.003 0.001 0.001 0.03 0.002 0.001 0.03 0.03 0.001 0.004 0.38	Steelmaking Method Test Type C Mn P S Si Cr Cu Mo Ni V Ti Nb B CE(IIW) CE(II

	BSM-1698		Heat	
	Heat		Test Type	
	Ferrite & Pearlite		Microstructure	
	79 HRBW		Hardness	
	Pass		Flattening Test	
	Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
	42,100	psi	Yield (Rt0.5)	
The second secon	70,500	psi	Tensile (Rm)	
	0.60	(Rt0.5/Rm)	Υ/Τ	
	42	%	Elongation (A)	

BSM-1698	S	Heat	
	tandard	Test	
1	Sample Details	Impact Test	
•	°C	Temp	
-	J		
	J	Impact	
_	J	Energy	
ı	AVG		
t	%		
L	%	% Shear	
•	%	hear	
ı	AVG		
	mm	Lateral Expansion	
1	mm		
1	mm		
i	AVG		

Additional Details:

- 🗸 We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in and that the results meet the corresponding requirements. accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B/C A/SA53-2012, and the purchase order requirements,
- \checkmark This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- ✓ No weld repairs have been performed on this product.
- ✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

PINANHOO

Kenton Dechant, P.Eng. Manager of Quality and R&D