

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.bri-steel.com

Seamless Carbon Steel Pipe

Product Standards: Production Method:

Product Heat Number:

BSM-1774

Product Size: 22XS

Production Date:

Certificate No.: MTR- 001045 Apr 17, 2014

Hot Expansion Product Heat Treatment: As-rolled

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

Product Markings MBRI-STEEL AND STATE OF THE REAL BROWN 11774 (SIDE # LENGTH MASS) 114.8Ib/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA | <API & L/C No.> API SPEC 5L NPS 22 XS 0.500 INCHWT GR B/X42 PSL1 SMLS 2014/04 NDE 1720PSI

BS			П
BSM-1774		Heat	
Heat		Test Type	
NPS 22 XS 0.500in. WT		Product Size	Product: Details
1		Pieces	
DRL		Length	
114.8	lb/ft	Mass	
웃	μR/hr	Geiger	
< 5	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	Z
Pass	WT	TU	Non-Destructive Testing
Pass	ASTM E213 ASTM	TU	tive Testing
Pass		ΕT	
Pass	1720 PSI/ 5 s Condition	HydroTest	
32.5° Bevel	S Condition	End	

		_		 	_
	BSM-1774	Heat		BSM-1774	
Blast Furnace; EAF Degas; Fully Killed		Stee		Heat	
C	Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method		NPS 22 XS 0.500in. WT	
Product 0.19	Heat	Test Type		NT	
0.19	0.19	С		1	
0.87	0.89	Mn		DRL	
0.87 0.011 0.007	0.89 0.014 0.008	Ъ	С	114.8	lb/ft
	0.008	S	Chemical Analysis (wt%)	OK.	μR/hr
0.22	0.22	Si	nalysis (v	<5	Gauss
0.03	0.03	Cr	/t%)	5	uss
0.06	0.06	Cu		Pass	Insp.
0.01	0.01	Мо		Pass	
0.03	0.03	Ni		Pass	TW
0.003		٧		Pass	ASTM
0.001		Ti			E213
0.001		Мþ		Pass	ASTM
5E.0 5E.0 E000.0 100.0 100.0 E00.0	0.0003	В		Pass	ASTM E213 ASTM 1720PSI/ 5 s Condition
0.35	ı	CE(IIW)			5 s C
0.35	T	CE(IIW) CE(CSA)		32.5° Bevel	ondition

BSM-1774 Heat Ferrite & Pearlite		Heat Test Type Microstructure	
75 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
42,600	psi	Yield (Rt0.5)	
68,000	psi	Tensile (Rm)	
0.63	(Rt0.5/Rm)	Υ/Τ	
50	%	Elongation (A)	

	BSM-1774		Heat
	1	Standard	Test
	1	Sample Details	Impact Test
	t	°C	Temp
	,	J	
	1	J	Impact
		J	Energy
	ı	AVG	
	1	%	
	1	%	% Shear
	1	%	ear
		AVG	
	-	mm	
	,	mm	Lateral Ex
		mm	I Expansion
	1	AVG	

Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements.
- √This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1
- No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

95 souden 2014 APR 24

Assistant QA Manager Paul Sowden, T.T.