

Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Hot Expansion

Product Heat Number:

Product Heat Treatment:

As-rolled

BSM-2025

Product Size: 24560

Production Date:

Certificate No.: MTR- 001358 Sep 22, 2014

Product Markings

Product Standards: Production Method:

HEAT BSM-2025 (PIPE # LENGTH MASS) 238.1Ib/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No. > API SPEC 5L NPS 24 SCH 60 0.969 INCHWT GR B PSL1 SMLS 2014/09 NDE 1900PSI ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A/SA106-2013 Grade B NDE, A/SA53-2012 Grade B Type S, NACE MR0175-2009 MR0103-2010

BSM-2025 Heat		Heat Test Type		
NPS 24 SCH 60 0.969in, WT		Product Size	Product: Details	
4		Pieces		
DRL		Length		***************************************
238.1	lb/ft	Mass		
G	μR/hr	Geiger		
<10	Gauss	Res, Mag.		
Pass	Insp.	Visual		
Pass		8	NC	
Ssed	ΨT	UT	on-Destruct	
Pass	ASTM E213 ASTM	4	Non-Destructive Testing	
Pass	ASTM	ET		
Pass	1900 PSI/ 5 s Condition	HydroTest		
Plain End	s Condition	End		

		-	,			
+K01				BSM-2025	Heat	
Heat Tost Type				BSM-2025 Blast rumace; EAF; Ladie Refining; Vacuum Degas: Fully Killed	Steelmal	
Microstructura				adle Refining; Vacuum	Steelmaking Method	
			Product 0.20 0.88 0.011 0.007 0.23 0.05	Heat	Test Type C	
3			0.20	0.18	С	
n			0.88	0.87	Mn	
7			0.011	0,009	P	***************************************
	Mechani		0.007	0.18 0.87 0.009 0.009 0.22	S	Chemical Analysis (wt%)
7	Mechanical Properties		0.23	0.22	Ω	Analysis (
*	ties		0.05	0.05	ţ	W1%)
			0.07	90.0	Cr	
1			0.01	0.01	Μo	
St. 1. 350 T. 1. 1. 777			0.03	0.03	2.	
1			0.003		٧	
;			0.001 0.001		7	
			0.001		Nb	
			0.0003	0.0003	8	
			0.0003 0.37 0.37	•	CE(IIW)	
			0.37	1	CE(IIW) CE(CSA)	
•					_	_

BSM-2025		Heat	85M-2025	неат
,	Standard	Test	Heat	
			Ferrite & Pearlite	Microstructure
1	Sample Details	impact Test	74 HRBW	Hardness
,	ိင်	Temp	Pass	Flattening Test
ι			Le	
1	۲.	Impact Energy	Longitudinal; 19.05 mm >	Ter 50
,	ړ	Energy	l; 19.05 n	Tension Test 50mm GL
ı	AVG		m × WT	
ŧ	%		_	<u> </u>
,	%	% Shear	36,100	Yield (Rt0.5) psi
f	%	ear	68	Tensi
	AVG		68,000	Tensile (Rm) psi
;	mm		0.53	Y/T (Rt0.5/Rm)
1	mm	Lateral Expansion		Rm)
t	mm AVG	kpansion	45	Elongation (A) %
1	AVG			on (A)

ı	<u>.</u>		,	•	1	ľ	ı	1	,	ı	ı	,	*	,	BSM-2025
AVG	m m	mm	AVG mm	AVG	%	%	AVG % %	AVG	_	_	-	۲	Sample Details	Statistatis	-
			***************************************				K					Š	Charles Dataile	N+1001011	
	Lateral Expansion	Lateral E			Shear	% Shea			Energy	Impact 6		Temp	impact Test	Test	Heat

Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A/SA106-2013 Grade B A/SA53-2012, and the purchase order requirements, and that the results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2010 Section 2.1

 \checkmark No weld repairs have been performed on this product.

 \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Tonya Lam, C.E.T.

Mill Test Certificate approved by:

Assistant QA Manager