

## Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

BSM-2146

Product Size: 16T80

Production Date: Nov 27, 2014

As-rolled

ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-2012 Hot Expansion Product Heat Treatment: Certificate No.: MTR- 001473

**Product Markings** 

**Product Standards:** Production Method:

HEAT BSM-2146 (PIPE # LENGTH MASS) 136.5lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No.> API SPEC 5L NPS 16 TRUE 80 0.844 INCHWT GR B PSL1 SMLS 2014/11 NDE 2500PSI

BSN			
BSM-2146		Heat	
Heat		Test Type	
NPS 16 TRUE 80 0.844in. WT		Product Size	Product: Details
4		Pieces	
DRL		Length	
136.5	lb/ft	Mass	
\$	μR/hr	Geiger	
<15	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	No
Pass	WT	TU	Non-Destructi
Pass	ASTM E213	TU	ctive Testing
Pass	ASTM	ET	(O)
Pass	2500 PSI/ 5 s	HydroTest	
Plain End	Condition	End	

						Chemical A	Analysis (v	vt%)									
Heat	Steelmaking Method	Test Type	C	Mn	P	S	Si	Cr	Cu	Mo	<u>Z</u>	<	Ti	Νb	В	CE(IIW)	CE(CSA)
BSM-2146	Blast Furnace; EAF; Ladle Refining; Vacuum	Heat	0.19	0.91	0.011	0.006	0.24	0.03	0.07	0.01	0.04				0.0003	1	ī
	Degas, ruly silled	Product	0.19	0.91	0.011	1 0.006	0.25	0.04	0.07	0.01	0.03	0.003	0.001	0.001	0.0003	0.36	0.36

BSN	Γ		Γ
1-2146		Heat	
Heat		Test Type	
Ferrite & Pearlite		Microstructure	
73 HRBW		Hardness	
Pass		Flattening Test	
Longitudinal; 25.4 mm x WT	50mm GL	Tension Test	Mechanical Properties
40,400	psi	Yield (Rt0.5)	
68,500	psi	Tensile (Rm)	1
0.59	(Rt0.5/Rm)	Υ/Τ	
47	%	Elongation (A)	
	Ferrite & Pearlite 73 HRBW Pass Longitudinal; 25.4 mm x WT 40,400 68,500	Heat         Ferrite & Pearlite         73 HRBW         Pass         Longitudinal; 25.4 mm x WT         40,400         68,500	Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rm)  Heat Ferrite & Pearlite 73 HRBW Pass Longitudinal; 25.4 mm x WT 40,400 68,500

BSM-214	1000	Heat
46		_
1	Standard	Test
ı	Sample Details	Impact Test
	റ്	Temp
·	L	
t	_	Impact
ı	L	Energy
ľ	AVG	
ı	%	
ı	%	% Shear
•	%	ear
	AVG	
	mm	
r	mm	Lateral Expansion
-	mm	xpansion
1	AVG	

## Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B A53-2012/SA53-2013, and the purchase order requirements, and that the results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1

✓ No weld repairs have been performed on this product.

 $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

✓ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.

Mill Test Certificate approved by:

Tonya Lam, C.E.T.

Assistant QA Manager