

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.bri-steel.com

Product Heat Number: BSM-2161 Product Size: 16STD Production Date: Dec 03, 2014

Production Method: ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B/C NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-Hot Expansion **Product Heat Treatment:** As-rolled Certificate No.: MTR- 001483

Product Standards:

Product:

Seamless Carbon Steel Pipe

Product Markings

HEAT BSM-2161 (PIPE # LENGTH MASS) 62.58lb/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No.> API SPEC 5L NPS 16 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2014/12 NDE 1680PSI

	BSM-2161		Heat	The second second
	Heat		Test Type	
	NPS 16 STD 0.375in. WT		Product Size	Product: Details
	Ľ		Pieces	
	DRL		Length	
	62.58	lb/ft	Mass	
57,557,5	<5	μR/hr	Geiger	
1000	<20	Gauss	Res. Mag.	
	Pass	Insp.	Visual	
	Pass		OD	No
200	Pass	WT	TU	Non-Destructive Testing
	Pass	ASTM E213 ASTM	UT	tive Testing
	Pass	ASTM	ET	
	Pass	1680 PSI/ 5 s	HydroTest	
The second secon	32.5° Bevel	s Condition	End	No. 10

					_	
Heat				BSM-2161	Heat	
Test Type		Degas; Fully Killed	Blast Furnace; EAF; I	Steelma		
Microstructure				Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method	
Har			Product 0.21 0.85	Heat	Test Type	
Hardness			0.21	0.20	С	
Flatten			0.85	0.87	Mn	
Flattening Test			0.014 0.012 0.26	0.013 0.011	Р	
	Mechanical Properties		0.012	0.011	S	Chemical Analysis (wt%
Tens	al Proper		0.26	0.25	Si	۱nalysis (۷
Tension Test	ties		0.04	0.04	Cr	vt%)
			0.07	0.06	Cu	
Yiek			0.01	0.01	Mo	
Yield (Rt0.5)			0.03	0.03	Z.	
Tensile (Rm)			0.004		<	
(Rm)			0.001		Ti	
۲/۲			0.001		Νb	
			0.0004	0.0003	В	
Elongation (A)			0.001 0.0004 0.37 0.37		CE(IIW) CE(CSA)	
າກ (A)			0.37	9	CE(CSA)	

BSM-2161		Heat	
,	Standard		
1	Sample Details	Impact Test	
-	°C	Temp	
1	J		
1	,		
	J	: Energy	
	AVG		
-	%		
ï	%	% Shear	
ī	%	ear	
ı	AVG		
ı	mm		
t	mm	Lateral Ex	
	mm	Expansion	
t	AVG		

Additional Details:

BSM-2161

Heat

Ferrite & Pearlite

78 HRBW

Pass

Longitudinal; 38.1 mm x WT 50mm GL

43,300 psi

72,000

psi

(Rt0.5/Rm) 0.60

42 %

 \checkmark We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B/C A53-2012/SA53-2013, and the purchase order requirements, and that the results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1.

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1

✓ No weld repairs have been performed on this product.

√ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Aros/2014

Tonya Lam, C.E.T.

Assistant QA Manager