

Product:

Seamless Carbon Steel Pipe

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Tel: 001 (780) 469-6603 Fax: 001 (780) 469-6986

www.bri-steel.com

Product Heat Number: BSM-2241 Product Size: 24S30 Production Date: Feb 11, 2015

Production Method: Hot Expansion **Product Heat Treatment:** As-rolled Certificate No.: MTR- 001579

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-2012

Product Markings

brirteel

HEAT BSM-2241 (PIPE # LENGTH MASS) 140.8lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No. > API SPEC 5L NPS 24 SCH 30 0.562 INCHWT GR B PSL1 SMLS 2015/02 NDE 1000PSI

_	-	_			_		_
DCM 2241	Heat			BSM-2241		Heat	
Blast Furnace: F	Stee			Heat		Test Type	
DCM 22/1 Black Furnace: FAF: Ladle Refining: Vacuum	Steelmaking Method			NPS 24 SCH 30 0.562in. WT		Product Size	Product: Details
11001	Test Type			. WT		P:	tails
0 0	С			2		Pieces	
0	Mn			DRL		Length	
0.30 0.80 0.011 0.003 0.31 0.03	Р	0		140.8	lb/ft	Mass	
2007	S	Chemical Analysis (wt%)		<5	μR/hr	Geiger	
2	Si	ıalysis (v		<10	Gauss	Res. Mag.	
2	Cr	/t%)			uss	Mag.	
0 0 0	Cu			Pass	Insp.	Visual	
200	Mo			Pass		OD	Z
2	N:			Pass	WT	TU	on-Destru
2004	<			Pass	ASTM E	TU	Non-Destructive Testing
000	Τi				ASTM E213 ASTM		ng
1000	qN			Pass		ET	
1000	В			Pass	1000 PSI/	HydroTest	
	CE(IIW)			3.	5 s C	tse	
	CE(IIW) CE(CSA)			32.5° Bevel	5 _S Condition	End	

		BSM-2241
	Cobra, Lawy Minera	Blast Furnace; EAF; Ladle Refining; Vacuum
	Product	Heat
	0.20	0.20
	0.86	0.86
	0.86 0.011 0.007 0.22	0.86 0.011 0.007
Mechani	0.007	0.007
Mechanical Propertion	0.22	0.24
rties	0.03	0.03
	0.08	0.07
	0.01	0.01
	0.03	0.03
	0.005	0.001
	0.001	0.001
	0.001	0.001 0.0004
	0.0002	0.0004
	0.36	
	0.36	ı

BS		_	
BSM-2241		Heat	
ı	Standard	Test	
-	Sample Details	Impact Test	
Ţ	°C	Temp	
-	J		
	J	Impact E	
	J	Energy	
-	AVG		
	%		
	%	% Shear	
ī	%	lear	
	AVG		
	mm		
	mm	Lateral Ex	
	mm	Expansion	
,	AVG		

Additional Details:

BSM-2241

Heat

Ferrite & Pearlite

77 HRBW

Pass

Longitudinal; 38.1 mm x WT

44,200

67,000

Heat

Test Type

Microstructure

Hardness

Flattening Test

Tension Test 50mm GL

Yield (Rt0.5)

Tensile (Rm)

psi

(Rt0.5/Rm) 0.66

ĭ

Elongation (A)

6 %

- We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1 API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B A53-2012/SA53-2013, and the purchase order requirements, and that the
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1
- ✓ No weld repairs have been performed on this product.
- \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

m feb/18/2015

Tonya Lam, C.E.T.

Assistant QA Manager