

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe

Product Heat Number:

Product Heat Treatment:

18STD

Production Date: Feb 18, 2015

BSM-2247

Product Size:

Certificate No.: MTR- 001587

Product Standards: Production Method: Hot Expansion

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-

As-rolled

Product Markings

HEAT BSM-2247 (PIPE # LENGTH MASS) 70.59lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No.> API SPEC 5L NPS 18 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2015/02 NDE 1640PSI

BS	Г		Г
BSM-2247		Heat	
Heat		Test Type	
NPS 18 STD 0.375in. WT		Product Size	Product: Details
4		Pieces	
DRL		Length	
70.59	lb/ft	Mass	
<5	μR/hr	Geiger	
<10	Gauss	Res. Mag.	
Pass	Insp.	Visual	
Pass		OD	N
Pass	WT	TU	on-Destruc
Pass	ASTM E213 ASTM	TU	Non-Destructive Testing
Pass	ASTM	ET	
Pass	1640 PSI/ 5 s Condition	HydroTest	37. 20.000
32.5° Bevel	Condition	End	

	BSM-2247	Heat	
Cagas, rolly silico	Blast Furnace; EAF; Ladle Refining; Vacuum	Steelmaking Method	
Product	Heat	Test Type	
0.19	0.18	С	
0.91	0.89	Mn	
0.029	0.014	Р	
0.005	0.006	S	Chemical
0.25	0.25	Si	Analysis (
0.03	0.03	Cr	wt%)
0.03	0.03	Cu	
0.00	0.00	Mo	
0.01	0.01	Ni	
0.007	0.004	٧	
0.030	-	Ti	
0.001	-	Nb	
0.0004	1	В	
0.35	1	CE(IIW)	
0.35	1	CE(CSA)	

Heat			Heat	
	Heat		Test Type	
	Ferrite & Pearlit		Microstructure	
	te		rē	
	78 HRBW		Hardness	
	Pass		Flattening Test	
	Longitudinal; 38.1 mm x WT	50mm GL	Tension Test	Mechanical Properties
	42,300	psi	Yield (Rt0.5)	
	65,500	psi	Tensile (Rm)	
	0.65	(Rt0.5/Rm)	۲/۲	
	40	%	Elongation (A)	
		Ferrite & Pearlite 78 HRBW Pass Longitudinal; 38.1 mm x WT 42,300 65,500	Heat Ferrite & Pearlite 78 HRBW Pass Longitudinal; 38.1 mm x WT 42,300 65,500 0.65	Test Type Microstructure Hardness Flattening Test Tension Test Yield (Rt0.5) Tensile (Rm) Y/T E 50mm GL psi psi (Rt0.5/Rm) Heat Ferrite & Pearlite 78 HRBW Pass Longitudinal; 38.1 mm x WT 42,300 65,500 0.65

Additional Details:

BSM-2247

Standard

Sample Details

ů

AVG

%

%

%

AVG

mm

mm

mm

AVG

 \checkmark We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1. API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B A53-2012/SA53-2013, and the purchase order requirements, and that the

√This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1

No weld repairs have been performed on this product.

 \checkmark This product has not come into contact with mercury during the Bri-Steel Manufacturing processes

 \checkmark This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Tonya Lam, C.E.T.

Assistant QA Manager