

## Mill Test Certificate

2125-64 Avenue, Edmonton, AB Canada T6P 1Z4 Bri-Steel Manufacturing Inc.

Tel: 001 (780) 469-6603

Fax: 001 (780) 469-6986 www.bri-steel.com

Feb 24, 2015

As-rolled Certificate No.: MTR-

Product Standards: ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B/C NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103Production Method:

**Hot Expansion** 

Product:

Seamless Carbon Steel Pipe

**Product Heat Number:** 

BSM-2255

Product Size: 16STD

Product Heat Treatment:

**Product Markings** 

HEAT BSM-2255 (PIPE # LENGTH MASS) 62.58Ib/ft ASTM/ASME A/SA106 GR B/C A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No.> API SPEC 5L NPS 16 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2015/02 NDE 1680PSI

Pass	Pass	Pass	Pass	Pass	<10	<b>%</b>	62.58	DRL	2	NPS 16 STD 0.375in. WT	Heat	BSM-2255
ASTN	ASTM E213 ASTM	WT A		Insp.	Gauss	μR/hr	lb/ft					
ET	F	디	00	Visual	Res. Mag.	Geiger	Mass	Length	Pieces	Product Size	Test Type	Heat
	? Testing	Non-Destructive Testing	No							Product: Details		

					•	Chemical Analysis (wt%)	۱) Analysis	wt%)									
Heat	Steelmaking Method	Test Type	С	Mn	Р	S	Si	Cr	Cu	Mo	Ni	٧	Ti	Nb	В	CE(IIW)	CE(CSA)
BSM-2255	Blast Furnace; EAF; Ladle Refining; Vacuum	Heat	0.20	0.87	0.009	0.005	0.23	0.05	0.03	0.01	0.01	0.005	ı	,	-	1	1
	Degas; rully Nileo	Product	0.21	0.90	0.016	0.004	0.23	0.04	0.03	0.00	0.01	0.005	0.036	0.001	0.0003	0.37	0.37

BS				BS	Г		Г
BSM-2255		Heat		BSM-2255		Heat	
ı	Standard	Test		Heat		Test Type	
	rd			Ferrite & Pearlite		Microstructure	
	Sample Details	Impact Test		rlite		ıre	
	t Test Details			78 HRBW		Hardness	
1	°C	Temp		Pass		Flattening Test	
,	J			Lc			Mechan
-	J	Impact Energy	300000000000000000000000000000000000000	Longitudinal; 38.1 mm x	50	Ten	Mechanical Properties
,	J	Energy	X0X0	al; 38.1 m	50mm GL	Tension Test	rties
,	AVG		THE SECOND SECOND	m x WT			
31	%	% Shear	1000000	4		Yie	
ı	%			45,000	psi	Yield (Rt0.5)	
1	%			72,0	р	Tensile (Rm)	
1	AVG			72,000	psi	le (Rm)	
1	mm			0.63	(Rt0.5/Rm)	۲/۲	
t	mm	Lateral Expansion			Rm) %		
1	mm	xpansion		40		Elongation (A)	
ı	AVG					on (A)	

## Additional Details:

- ✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B/C A53-2012/SA53-2013, and the purchase order requirements, and that the results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1.
- √ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1
- ✓ No weld repairs have been performed on this product.
- $\checkmark$  This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.
- $\checkmark$  This certificate represents a quality control system that is compliant with EN 10204:2004 Type 3.1.

Mill Test Certificate approved by:

Tonya Lam, C.E.T.

Assistant QA Manager