

Mill Test Certificate

Bri-Steel Manufacturing Inc. 2125-64 Avenue, Edmonton, AB Canada T6P 1Z4

Tel: 001 (780) 469-6603 Fax: 001 (780) 469-6986

www.bri-steel.com

Product: Seamless Carbon Steel Pipe Product Heat Number: BSM-2291 Product Size: 18STD

Product Heat Treatment: As-rolled Certificate No.: MTR-

Mar 10, 2015

ASME B36.10-2004, API 5L-45th Ed. Grade B/X42 PSL1, ASTM/ASME A106-2014/SA106-2013 Grade B NDE, A53-2012/SA53-2013 Grade B Type S, NACE MR0175-2009 MR0103-

Product Standards:

Production Method:

Hot Expansion

Product Markings

bristeel

HEAT BSM-2291 (PIPE # LENGTH MASS) 70.59lb/ft ASTM/ASME A/SA106 GR B A/SA53 GR B NACE MR0175/MR0103 MADE IN CANADA <API & L/C No.> API SPEC 5L NPS 18 STD 0.375 INCHWT GR B/X42 PSL1 SMLS 2015/03 NDE 1490PSI

	BSM-2291		Heat	
	Heat		Test Type	
	NPS 18 STD 0.375in. WT		Product Size	Product: Details
	5		Pieces	
	DRL		Length	
	70.59	lb/ft	Mass	
	<5	μR/hr	Geiger	
	<10	Gauss	Res. Mag.	
	Pass	Insp.	Visual	
	Pass		OD	No
	Pass	TW	TU	n-Destruct
	Pass	ASTM E213 ASTM	TU	Non-Destructive Testing
1	Pass		땁	
	Pass	1490 PSI/ 5 s	HydroTest	
	32.5° Bevel	s Condition	End	

						Chemical Analysis (wt%)	Analysis (v	wt%)									
Heat	Steelmaking Method	Test Type	С	Mn	Р	S	Si	Cr	Cu	Мо	<u>Z</u> .	<	Ti	Мb	В	(WII)30	CE(CSA)
BSM-2291	Blast Furnace; EAF; Ladle Refining; Vacuum	Heat	0.18	0.89	0.014	0.006	0.25	0.03	0.03	0.00	0.01	0.004	,	1	1	1	ı
	Cegas, raily rilled	Product	0.20	0.89	0.019	0.007	0.24	0.03	0.03	0.01	0.01	0.006	0.031	0.001	0.0004	0.36	0.36

BSM-2291		Heat		BSM-2291		Heat	
	Test Standard		2	Heat		Test Type	
100	dard	Test		Ferrite & Pearlite		Microstructure	
	Samp	lmp		arlite		ture	
	Sample Details	Impact Test		76 HRBW		Hardness	
	°C	Temp	A 0.0 1	Pass		Flattening Test	
=	J			- 1	5(Mechanical Properties
1	J	Impact Energy	0.0000000000000000000000000000000000000	Longitudinal; 38.1 mm x		Ten	
1	J	Energy	Energy); 38.1 mr	50mm GL	Tension Test 50mm GL	
1	AVG			m x WT			
	%					Yie	
	%	% Shear		43,000	psi	Yield (Rt0.5)	
1	%	near		69		Tensi	
-	AVG			69,500	psi	Tensile (Rm)	
ı	mm	Lateral E		0.62	(Rt0.5/Rm)	1/4	
,	mm			2	/Rm)	_	6
3	mm	Lateral Expansion		40	%	Elongation (A)	
	AVG					on (A)	

Additional Details:

✓ We hereby certify that this pipe product was manufactured, sampled, tested and inspected by Bri-Steel Manufacturing Inc. in accordance with results meet the corresponding requirements. Bri-Steel Manufacturing is registered and certified to ISO-9001:2008 and API Q1. API 5L-45th Ed., ASTM/ASME A106-2014/SA106-2013 Grade B A53-2012/SA53-2013, and the purchase order requirements, and that the

√ This pipe product meets the sour service requirements of NACE MR0175/ISO 15156-2:2009 Annex A2 for Region 3 Sour Service-2009 NACE MR0103-2012 Section 2.1

✓ No weld repairs have been performed on this product.

√ This product has not come into contact with mercury during the Bri-Steel Manufacturing processes.

 \checkmark This certificate represents a quality control system that is compliant with EN 10204;2004 Type 3.1.

Mill Test Certificate approved by:

Than MAR/12/2015

Tonya Lam, C.E.T.

Assistant QA Manager